



## HBR

## REFLECTOR HIGH BAY

PROJECT :

NOTE :

COMPANY NAME:

TYPE:

DATE:

CATALOG NUMBER:

ITEM CODE

WATT

CCT

BEAM ANGLE

VOLTAGE

OPTION

### SPECIFICATION

#### DIE CAST ALUMINIUM

POWER EFFICIENCY: > 90%

THD < 15%

CCT: 4000K / 5000K

LUMEN OUTPUT: >130LM/W

IP GRADE: IP54

CRI > 80

WORKING TEMPERATURE: -25°C ~+50°C

0~10V DIMMING OPTION

BEAM ANGLE: 120° / 90° /60°

5 YEAR WARRANTY

### FEATURES

#### CONSTRUCTION

- Die cast aluminium support with extruded aluminium fins
- Spun aluminium reflector
- Natural aluminium color
- Polycarbonate lens standard
- Standard 120° beam angle, others optional
- Reflector ship separately
- IP54

#### MOUNTING

- Die casting loop

#### ELECTRICAL

- 120/277V or 347V
- 0-10V dimming option
- PF> 0.95
- THD ≤ 15 %
- Ambient: -20°C~+50°C

#### COMPLIANCE

- ULc
- DLC
- ICES-005
- 5 Year Warranty
- IEC 60929 Annex E



### MODELS

Item Code	Watts(W)	Lumens ( LM)	CCT	Voltage
HBR-150W-XXK-XXXV	150	18000	4000K / 5000K	120-277 Or 347
HBR-200W-XXK-XXXV	200	24000	4000K / 5000K	
HBR-240W-XXK-XXXV	240	28800	4000K / 5000K	

### DIMENSION

Watts(W)	Dimension ( D* H * L)
150	8.6 X 13.2 X 19.7
200	7.2 X 13.2 X 19.7
240	11.2 X 13.2 X 19.7

