

HBU

UFO HIGH BAY

PROJECT :

NOTE :

COMPANY NAME:

TYPE:

DATE:

CATALOG NUMBER:

ITEM CODE

WATT

CCT

BEAM ANGLE

VOLTAGE

MOUNTING

SPECIFICATION

POWER EFFICIENCY: > 90%

CCT: 4000K, 5000K

COLOR RENDERING INDEX: CRI>80

BEAM ANGLE: 120°

MATERIAL: AL+LGP+PS

WORKING TEMPERATURE: -20 °C ~ +45 °C

STORAGE TEMPERATURE: -25 °C ~ +65 °C

IP GRADE : IP65



WORKING LIFESPAN: LM80-50,000HRS

LUMEN OUTPUT: >130LM/W

2 OPTIONAL LENS: CLEAR LENS / GLOSSY LENS

2 HOUSING SIZE

5 YEAR WARRANTY



FEATURES

CONSTRUCTION

- Die cast aluminium heat sink provides passive cooling
- Powder coat paint black
- Polycarbonate lens standard
- Stainless steel hardware
- 3ft cabtire 3/18 AWG
- Standard 120° beam angle, others optional
- 2 housing size

MOUNTING

- Standard stainless steel loop
- Yoke mount [optional]

ELECTRICAL

- 120/277V or 347V
- 0-10V dimming option
- PF> 0.95
- THD ≤ 15 %
- Ambient: -20°C~+50°C

COMPLIANCE


- ULc
- DLC
- ICES-005
- 5 Year Warranty
- wet location
- IEC 60929 Annex E



MODELS

Item Code	Watts(W)	Lumens (LM)	CCT	Weight (lbs)	Voltage
HBU-100W-40K-XXX HBU-100W-50K-XXX	100 100	12200 12300	4000 5000	6.6	120-277 Or 347
HBU-150W-40K-XXX HBU-150W-50K-XXX	150 150	18300 18450	4000 5000	8.8	
HBU-200W-40K-XXX HBU-200W-50K-XXX	200 200	24000 24600	4000 5000	13.2	
HBU-240W-40K-XXX HBU-240W-50K-XXX	240 240	29280 29520	4000 5000	15.4	

ACCESSOIRES



**YOKE MOUNTING OPTIONAL:
AHBU-Y-100/150/200/240**