

	<h2 style="margin: 0;">TUA / T8 ALUMINIUM REFLECTOR TUBE</h2>	
	PROJECT :	
	NOTE :	
	COMPANY NAME:	
TYPE:		DATE:
CATALOG NUMBER: <hr/> <div style="display: flex; justify-content: space-between; font-size: small;"> <span>ITEM CODE</span> <span>WATT</span> <span>CCT</span> <span>BEAM ANGLE</span> <span>VOLTAGE</span> <span>OPTION</span> </div>		

### SPECIFICATION

**LED TUBE T8 DOUBLE END / SINGLE END BY PASS**  
**ALUMINIUM HEAT DISSIPATOR REFLECTOR**  
**POLYCARBONATE LENS**  
**INPUT VOLTARE 100V~277V 60HZ**  
**POWER EFFICIENCY: >90%**  
**THD: ≤20%**  
**COLOR TEMPERATURE 4000K,5000K**  
**WORKING TEMPERATURE -25°C~+45°C**  
**IP GRADE: IP44**  
**HUMIDITY: 95%RH**  
**WORKING LIFESPAN: LM80-50,000HR**  
**LUMEN OUTPUT>120LM/W**  
**STARTING TIME<0.5S**  
**CRI>80**  
**5 YEAR WARRANTY**

### MODEL

Item code	Description
TUA-D-4FT-18W-XXK-120-B	Double end 4ft LED tube, by pass, CCT 4000/5000K, 120lm/w, voltage120V
TUA-4FT-18W-XXK-120-B	Single end 4ft LED tube, by pass, CCT 4000/5000K, 110lm/w, Voltage 120V

### FEATURES

#### CONSTRUCTION

- Aluminium heat dissipator reflector
- IP44
- Humidity: 95%RH
- Polycarbonate lens
- Operating temperature -25°C ~ +45°C

#### ELECTRICAL

- Double end or single end feed
- Bypass only
- THD < 20%

#### MOUNTING

- Fit to T8 standard socket

#### COMPLIANCE

- cUL
- DLC

